



**Ningbo Beilun Door Parts CO.,LTD.**  
**GDP International Trade CO.,LTD.**

**ADD.: #59Jiufeng District,Beilun,315080,Ningbo,China**

**T E L: 86-138 1981 1084**

**86-133 8665 9112**

**F A X: 86-574-8691 0916**

**E-mail: znancycn@tom.com**

**gdp@gdpdoor.com**

**Http://www.gdpdoor.com**



**GDP International Trade CO.,LTD.**

打造车库门配件第一品牌



## Hinges



**GDP1001**

1# Hinge

Bright zinc plated 14 gauge steel hinge



**GDP1002**

2# Hinge

Bright zinc plated 14 gauge steel hinge



**GDP1003**

3# Hinge

Bright zinc plated 14 gauge steel hinge



**GDP1004**

4# Hinge

Bright zinc plated 14 gauge steel hinge



**GDP1005**

5# Hinge

Bright zinc plated 14 gauge steel hinge



## Springs & Cables



**GDP6001**

Extension Spring Machine

1"bore with 1/4"keyway  
Malleable iron adjustable coupler  
Coupler halves assembled  
Silcer rust inhibitor coating




**Springs**

All kinds of torsion spring and Extension spring  
Adope time quality spring  
Quenching treatment  
Different kinds of doors adopt different extension spring



**Tracks**

Diameter 1"  
Square stick



**PVC Seals**

PVC material. Has been through 12002-89



**Screws**

For use to different kinds of  
standard parts in garage doors



## Hinges



**GDP1014**

### Finger Protection Hinge(Euro.)

Bright zinc plated steel  
14 gauge roller carrier  
14 gauge base plate  
Mounting holes on 3" centers (vertically)  
Adjustment 3/8" minimum to 3" maximum



**GDP1015**

### Height Finger Protection Hinge

Height finger protection hinge  
Bright zinc plated steel  
Adjustment 3/8" minimum to 3-1/2" maximum  
For use with two sides hinge to protection finger



**GDP1016**

### Central Hinge

Bright zinc plated 14 gauge steel hinge  
Mounting holes on 1-5/8" centers (vertically)  
Holes sizes for 1/4" diameter screw



**GDP1017**

### Finger Protection Central Hinge (Euro.)

Bright zinc plated 14 gauge steel hinge  
Mounting holes on 2-5/8" centers (vertically)  
Holes sizes for 1/4" diameter screw



**GDP1018**

### Height Finger Protection Central hinge

Add to high finger protection center hinge  
Mounting holes on 2-3/8" centers (vertically)  
Holes sizes for 1/4" diameter screw



## Handles & Locks



**GDP5016**

### Outside Knob

Bright zinc plated steel  
Use with autolatch locks & keyed t-handles



**GDP5017**

### Residential Slide Lock

Bright zinc plated steel  
Designed for 2" or 3" track  
Slotted mounting holes



**GDP5018**

### Commercial Slide Lock

7-1/2" lock bar with 11/16" long posts  
360 degree rotation  
Includes mounting fasteners  
Includes adjustable spacers to fit door thickness from 3/4"-2"



**GDP5019**

### Commercial Lock

Used for opening door on door  
This is knob inside door  
Fit for panel door of 40mm thickness



**GDP5020**

### Plastic Inside Handle

Plastic Inside Handle





## Springs & Cables



**GDP6001**

### 15" Pusher Springs

Push down bumper spring-15"  
Overall length:15"  
12gauge bracket for 3/8" bolts  
6" Travel  
Approximate compression:10lb/in  
2" diameter bumper  
Zinc plated steel



**GDP6002**

### 27" Pusher Springs

Push down bumper spring-27"  
Overall length:27"  
12gauge bracket for 3/8" bolts  
15" Travel  
Approximate compression:10lb/in  
2" diameter bumper  
Zinc plated steel



**GDP6003**

### #1 Chain Hoist

6.6:1 reduced drive



**GDP6004**

### #3 Chain Hoist

3:1 reduced drive



**GDP6005**

### #5 Chain Hoist

Model J.R



## Hinges



**GDP1006**

### 6# Hinge

Bright zinc plated 14 gauge steel hinge



**GDP1010**

### Adjustable Top Roller

Top Bracket with Roller  
Bright zinc plated 12 gauge, 2" x 11 ball  
nylon roller  
Roller rating: 75-lb load @ 15,000 12"  
door cycles



**GDP1011**

### Finger Protection Hinge

Bright zinc plated steel  
14 gauge roller carrier  
14 gauge base plate  
Mounting holes on 3" center (vertically)  
Adjustment 3/8" minimum to 3" maximum



**GDP1012**

### Commercial Adjustable Hinge

Bright zinc plated steel  
12 gauge roller carriers  
Mounting holes on 4-3/4" center  
Adjustment 7/16" minimum to 3-1/2"  
maximum



**GDP1013**

### Adjustable Hinge

Bright zinc plated steel  
14 gauge roller carrier  
14 gauge base plate  
Mounting holes on 3" centers (vertically)  
Adjustment 3/8" minimum to 3" maximum



## Brackets



**GDP3038**

### Spring Adjust Bracket

Bright zinc plated 12 ga. steel  
For 1-3/4 To 2-5/8 ID Springs



**GDP3039**

### Central Bearing Bracket commercial

1. Bright zinc plated 10ga. steel  
2. Bright zinc plated 8ga. steel.  
1. 3-12" Spring Anchor with bearing  
2. 5" Spring Anchor with bearing  
3. 5-5/8" Spring Anchor with bearing  
4. 6-3/8" Spring Anchor with bearing



**GDP3040**

### Adjust Bracket Commercial

Bright zinc plated 8Ga. Steel  
Adjustable center line from 3"-6"  
Available in either RH or LH flange  
Bearing not included



**GDP3041**

### Commercial Bearing Bracket

Bright zinc plated 8Ga. steel  
1, 4" set for steel jamb  
2, 5" set for steel jamb  
3, 6" set for steel jamb

**GDP** GDP International Trade CO.,LTD.



## Brackets



**GDP3023-1**

### Double Hole Side Bracket

Bright zinc plated 12Ga. steel  
A pair of holes' center distance is 2-3/16"  
Adjustment 3/8" minimum to 2-1/2"  
maximum



**GDP3024**

### Commercial Side Bracket

Bright zinc plated 11 Ga. steel  
Adjustment 3/4" minimum to 7-1/2"  
maximum



**GDP3025**

### Double Hole Side Bracket (commercial)

Bright zinc plated 11Ga. steel  
A pair of holes' center distance is 1-3/16"  
Adjustment 3/4" minimum to 7-1/2"  
maximum



**GDP3026**

### Flag Bracket

Bright zinc plated 14Ga. steel  
A pair of holes' center distance is 1-3/16"  
Adjustment 2" minimum to 4" maximum  
Use for joint track



**GDP3027**

### Universal Slotted Knife Angle

Bright Zinc plated 14Ga. steel  
A pair of holes' center distance is 1-3/16"  
Adjustment 2" minimum to 4" maximum  
Use for joint track  
Perforated Angle for Commercial Door





## Brackets



**GDP3028**

### Commercial Angle

Bright zinc plated 14ga .steel  
A pair of holes' center distance is 2-3/16"  
Adjustment 2" minimum to 4" maximum  
Perforacted Angle for Commercial Door



**GDP3029**

### Vertical Angle

Bright zinc plated 14Ga. Steel



**GDP3030**

### Perforacted Angle

Bright zinc plated 14Ga. Steel



**GDP3031**

### Tray Protection Epuip

Bright zinc plated 12Ga. Steel



**GDP3032**

### Residential Bearing Bracket

Bright zinc plated 10Ga. Steel  
3-3/8" Spring Anchor With Bearing



## Brackets



**GDP3033**

### EBF Bracket

Bright zinc plated 12 Ga.teel  
3-3/8" Spring Anchor With Bearing



**GDP3034**

### Commercial Bearing Bracket

1. Bright zinc plated 10 Ga steel  
2. Bright zinc plated 8Ga steel  
1. 3-1/2" Spring Anchor with bearing  
2. 5" Spring Anchor with bearing  
3. 5-5/8" Spring Anchor with bearing  
4. 6-3/8" Spring Anchor with bearing



**GDP3035**

### Flat Bearing Bracket

Bright zinc plated 8 Ga steel



**GDP3036**

### Central Bearing Bracket

Bright zinc plated 10 Ga steel  
3-3/8" Spring Anchor With Bearing



**GDP3037**

### Residential Central Bearing Bracket

Bright zinc plated 10 Ga steel  
3-3/8" Spring Anchor With Bearing



## Brackets



**GDP3015**

### Outside Hookup Bottom Bracket

Outside hook up bottom bracket  
Bright zinc plated 12 ga. steel  
Fits door thickness from 3/8"-2"



**GDP3016**

### Outside Hookup Bottom Bracket

Outside hook up bottom bracket  
Bright zinc plated 12 ga. steel  
Fits door thickness from 3/8"-2"



**GDP3021**

### Single Hole Side Bracket

Bright zinc plated 14 ga. steel  
1. Adjustment 3/4" minimum to 3-3/8" maximum  
2. Adjustment 1-3/8" minimum to 4-3/4" maximum  
1. Adjustment 1-3/4" minimum to 5-3/8" maximum



**GDP3022**

### Triangle Side Bracket

Bright zinc plated 14 Ga. steel  
Adjustment 1-1/2" minimum to 3-3/8" maximum



**GDP3023**

### Double hole side bracket

1. Bright plated 14 Ga. steel  
2. Bright plated 12 Ga. steel  
A pair of holes' center distance is 1-3/16"  
Adjustment 2" minimum to 4" maximum



## Spring Fittings & Drums



**GDP4001**

### 1-3/4" Spring Fitting

Universal thread for use in either LH or RH Wound springs  
Maximum wire size - .295" diameter  
Set includes (1) winding & (1) stationary  
Color coded winding fittings  
(2) 3/8"-16" 1" hardening cup point set screws installed  
For use on 1" tube or solid shaft-max 30ft\*lbs set screw torque



**GDP4002**

### 2" Spring Fitting

Universal thread for use in either LH or RH wound springs  
Maximum wire size - .3056" diameter  
Set includes (1) winding & (1) stationary  
Color coded winding fittings  
(2) 3/8"-16" 1" hardening cup point set screws installed  
For use on 1" tube or solid shaft-max 30ft\*lbs set screw torque



**GDP4003**

### 2-5/8" Spring Fitting

Universal thread for use in either LH or RH wound springs  
Maximum wire size - .331" diameter  
Set includes (1) winding & (1) stationary  
Color coded winding fittings  
(2) 3/8"-16" 1/2" hardening cup point set screws installed  
For use on 1" tube or solid shaft-max 30ft\*lbs set screw torque



**GDP4004**

### 3-3/4" Spring Fitting

1" bore; 1-1/4" bore use part #1314  
Universal thread for use in either LH or RH wound springs  
Maximum wire size - .4062" diameter  
Set includes (1) winding & (1) stationary  
Color coded winding fittings  
(2) 3/8"-16" 1" hardening cup point set screws installed  
For use on 1" tube or solid shaft-max 30ft\*lbs set screw torque  
Available with either long or shore ears on stationary fitting  
Can be combined with 6" spring fittings for duplex assembly



**GDP4005**

### 5-1/4" Spring Fitting

Single thread for LH & RH wound springs  
Set includes (2) winding (2) stationary  
Color coded winding fittings  
(2) 3/8"-16" 1-1/2" hardening cup point set screws installed  
For use on 1" tube or solid shaft-max 30ft\*lbs set screw torque  
Available with either long or shore ears on stationary fitting  
Can be combined with 6" spring fittings for duplex assembly





## Spring Fittings & Drums



**GDP4006**

### 6' Spring Fitting

1" bore (1-1/4" bore use part #1404)  
 Single thread for LH&RH wound springs  
 Maximum wire size- 4375" diameter  
 Set includes (2) winding & (1) stationary  
 Color coded winding & stationary fittings  
 3/8"-16" 2" hardened cup point set screws installed  
 For use on 1" tube or solid shaft-max 30ft" lbs set screw torque  
 Can be combined with 6" spring fittings for duplex assembly



**GDP4011**

### 400-8 Standard Lift

Maximum door height.....8' 1"  
 Rated lifting weight per drum.....265LBS  
 Maximum cable diameter.....1/8"  
 3/8-16" 1" hardened cup point set screws installed  
 Use on 1" tube



**GDP4012**

### 400-11 Standard Lift

Maximum door height.....11' 1"  
 Rated lifting weight per drum.....300LBS  
 Maximum cable diameter.....5/32"  
 3/8-16" 1" hardened cup point set screws installed  
 Use on 1" tube or solid shaft with 1/4" keyway



**GDP4013**

### 400-12 Standard Lift

Maximum door height.....12' 12"  
 Rated lifting weight per drum.....375LBS  
 Maximum cable diameter.....5/32"  
 3/8-16" 1" hardened cup point set screws installed  
 Use on 1" tube or solid shaft with 1/4" keyway



**GDP4014**

### 5250-18 Standard Lift

Maximum door height.....18' 1"  
 Rated lifting weight per drum.....750LBS  
 Maximum cable diameter.....3/16"  
 3/8-16" 1" hardened cup point set screws installed  
 Use on 1" tube or solid shaft with 1/4" keyway



## Brackets



**GDP3010**

### Quick Close Fixture

Reduces headroom requirement by 1-1/2" to 2-1/2"  
 Solve low headroom problems when installing  
 garage door openers  
 Serves same purpose as double track hardware:  
 add when needed  
 Used at initial installation or easily add to existing  
 installation



**GDP3011**

### Adjustment Bottom Bracket

Double deck  
 Cushion and counter-shock  
 For 2" track with 7/16" diameter roller stem  
 First door thickness from 1-3/8"-2"  
 Load weight: 500lbs



**GDP3012**

### Bottom Bracket-Commercial

Bright zinc plated 14 ga. Steel  
 For 2" track with 7/16" diameter roller stem  
 Milford pin cable attachment  
 First door thickness from 1-3/8"-2"  
 Load weight: 1000lbs



**GDP3013**

### Sure-stop Bottom Brackets-2" Track

Hold door in event of cable failure  
 Handles door up to 1650 lbs  
 Recommended for doors with over 100 lbs  
 open door weight  
 Add 4" to cable leng when using this device  
 instructions included



**GDP3014**

### Sure-stop Bottom Brackets-3" Track

Hold door in event of cable failure  
 Handles door up to 1650 lbs  
 Recommended for doors with over 100 lbs  
 open door weight





## Brackets



**GDP3003**

Top Bracket Residential(single screw)

Bright zinc plated steel  
14 gauge roller carrier  
15 gauge base plate  
Mounting holes on 3"centers(vertically)  
Adjustment 3/8" minimum  
to 3-3/8" maximum



**GDP3004**

Top Bracket Commercial

Bright zinc plated steel  
12 gauge roller carrier  
12 gauge base plate  
Mounting holes on 4-3/4"  
centers(vertically)



**GDP3005**

Bottom Bracket-Residential

Bright zinc plated 14 ga. Steel  
For 2" track with 7/16" diameter roller stem  
Milford pin cable attachment  
First door thickness from 1-3/8"-2"  
Load weight:500lbs



**GDP3006**

Bottom Bracket-Residential

Bright zinc plated 14 ga. Steel  
For 2" track with 7/16" diameter roller stem  
Milford pin cable attachment  
First door thickness from 1-3/8"-2"  
Load weight:500lbs



**GDP3007**

Bottom Bracket-Commercial

Bright zinc plated 14 ga. Steel  
For 2" track with 7/16" diameter roller stem  
Milford pin cable attachment  
First door thickness from 1-3/8"-2"  
Load weight:800lbs



## Spring Fittings & Drums



**GDP4015**

800-32 Standard Lift

Maximum high lift.....32' 1"  
Rated lifting weight per drum.....1000lbs



**GDP4016**

400-54 HI-Lift Cable Drums

Maximum high lift.....54"  
Maximum door height.....150"+Hi Lift  
Rated lifting weight per drum.....500LBS  
Maximum cable diameter.....3/16"  
3/8-16\*1"hardenes cup point set screws installed  
Use on 1" tube or solid shaft with 1/4"keyway



**GDP4017**

5250-54 HI-Lift Cable Drums

Maximum high lift.....54"  
Maximum door height.....108"+Hi Lift  
Rated lifting weight per drum.....500LBS  
Maximum cable diameter.....3/16"  
3/8-16\*1"hardenes cup point set screws installed  
Use on 1" tube or solid shaft with 1/4"keyway



**GDP4018**

5750-120 HI-Lift Cable Drums

120 HI-LIFT  
Maximum hi-lift:164"  
Capacity:500 lbs per drum  
Maximum cable size:3/6"



**GDP4019**

6375-164 HI-Lift Cable Drums

164 HI-LIFT  
Maximum hi-lift:164"  
Capacity:1,000lbs per drum  
Maximum cable size:1/4"



## Spring Fittings & Drums



**GDP4021**

### 143-11 Cable Drums

Maximum door height.....11' 1"  
 Rated lifting weight per drum.....425LBS  
 Maximum cable diameter.....3/16"  
 3/8-16\*1"hardenes cup point set screws installed  
 Use on 1" tube or solid shaft with 1/4"keyway



**GDP4022**

### 236-18 Cable Drums

Maximum door height.....8' 1"  
 Rated lifting weight per drum.....500LBS  
 Maximum cable diameter.....3/16"  
 3/8-16\*1"hardenes cup point set screws installed  
 Use on 1" tube or solid shaft with 1/4"keyway




**GDP4023**

### 329-28 Cable Drums

Maximum door height.....28' 1"  
 Rated lifting weight per drum.....1100LBS  
 Maximum cable diameter.....1/4"  
 3/8-16\*1"hardenes cup point set screws installed  
 Use on 1" tube or solid shaft with 1/4"keyway



## Handles & Locks



**GDP5001**

### Plastic Outside Handle

Door Outside Handle  
 ABS Plastic



## Rollers & Pulleys



**GDP2012**

### Bearing

1"bore, 2"o.d.  
 Rated load:250-lb@10,000 8" door cycles



**GDP2013**

### Flanged Nylon Bushing

1"bore, 2"o.d.  
 Rated load:250-lb@10,000 8" door cycles



## Brackets



**GDP3001**

### Double Top Bracket

Low top bracket headroom



**GDP3002**

### Top Bracket Residential(double screw)

Bright zinc plated steel  
 14gauge roller carrier  
 14gauge plated steel  
 Adjustment3/8"minimum  
 to3-3/8"maximum





## Rollers & Pulleys



**GDP2006**

### Rollers 2-7-10

2"10 ball steel roller  
7"stem  
Rating:75-lb load@ 15,000 12' door cycles



**GDP2007**

### Rollers 3-4-10

3"10 ball steel roller  
4"stem  
Rating:150-lb load@50,000 12" door cycles



**GDP2008**

### Rollers 3-7-10

3"10 ball steel roller  
4"stem  
Rating:150-lb load@ 50,000 12"door cycles



**GDP2010**

### 3" Pulleys

Bright zinc plated steel  
Bored for 3/8" diameter bolt  
Hardened inner race  
Max.cable diameter



**GDP2011**

### 4" Pulleys

Bright zinc plated steel  
Bored for 3/8" diameter bolt  
Hardened inner race  
Max.cable diameter 1/4"



## Handles & Locks



**GDP5002**

### Plastic Outside Handle

Door Outside Handle  
ABS Plastic



**GDP5003**

### Inside Handle

Bright zinc plated 14Ga.steel  
Door inside Handle



**GDP5004**

### Outside Handle

Bright zinc plated 14Ga.steel



**GDP5005**

### Lift Handle

Lift Handle - Closed Grip



**GDP5010**

### Emergency Lock

Cross key,copper core,one key to one lock installation  
convenient,generally install on the domestic door



## Handles & Locks



**GDP5011**

### Emergency Lock

Pipe key, copper core, one key to one lock installation convenient, generally install on the domestic door



**GDP5012**

### Emergency Lock

Pipe key, copper core, one key to one lock installation convenient, generally install on the domestic door



**GDP5013**

### T-handle lock

Bright chrome finished  
Zinc plated 5/16" square \*4" long shaft, 90 degree rotation



**GDP5014**

### Auto Lock

Bright zinc plated steel and spring  
13 gauge base plate  
11 gauge flipper arm



**GDP5015**

### Bump a Shot Slice

Bright zinc plated steel 14 Ga  
1-4/2" long slots for adjustment



## Rollers & Pulleys



**GDP2001**

### Rollers 2-4-N

2" nylon roller  
4" zinc plated stem  
Rating: 50-lb load @ 10,000 8' door cycles



**GDP2002**

### Rollers 2-4-11-N

2" 11 ball nylon roller  
4" zinc plated stem  
Rating: 75-lb load @ 15,000 12' door cycles



**GDP2003**

### Rollers 2-7-11-N

2" 11 ball nylon roller  
7" zinc plated stem  
Rating: 75-lb load @ 15,000 12' door cycles



**GDP2004**

### Rollers 2-4-7

2" 7 ball steel roller  
4" stem  
Rating: 35-lb load @ 10,000 8' door cycles



**GDP2005**

### Rollers 2-4-10

2" 10 ball steel roller  
4" stem  
Rating: 75-lb load @ 15,000 12' door cycles